

*Powered by Universal Speech Solutions LLC*



# Yandex SS Plugin

## Administrator Guide

---

Revision: 2

Distribution: Debian / Ubuntu

Created: November 19, 2018

Last updated: December 24, 2018

Author: Arsen Chaloyan

# Table of Contents


1	Overview.....	3
1.1	Applicable Versions.....	3
1.2	Supported Distributions .....	3
1.3	Authentication.....	3
2	Installing Deb Packages Using Apt-Get .....	4
2.1	Repository Configuration .....	4
2.2	GnuPG Key.....	4
2.3	Repository Update .....	4
2.4	Yandex SS Plugin Installation .....	4
3	Installing Deb Packages Manually.....	6
3.1	Package List.....	6
3.2	Package Installation Order.....	7
4	Obtaining License .....	8
4.1	License Type.....	8
4.2	Node Information.....	8
4.3	License Installation .....	8
5	Obtaining Service Credentials .....	9
5.1	Service Subscription .....	9
5.2	Installation of Credentials .....	9
6	Configuring Server and Plugin .....	10
6.1	Plugin Factory Configuration .....	10
6.2	Logger Configuration .....	10
6.3	Yandex SS Plugin Configuration.....	10
7	Validating Setup.....	11
7.1	Setting up Folder ID .....	11
7.2	Launching Server.....	11
7.3	Launching Client.....	12

# 1 Overview

This guide describes how to obtain and install binary packages for the Yandex Speech Synthesis (SS) plugin to the UniMRCP server on Debian-based Linux distributions. The document is intended for system administrators and developers.


## 1.1 Applicable Versions

Instructions provided in this guide are applicable to the following versions.

 UniMRCP 1.6.0 and above  
UniMRCP Yandex SS Plugin 1.0.0 and above

## 1.2 Supported Distributions

UniMRCP binary packages are currently available only for x86\_64 (64-bit) architecture.

Operating System	32-bit	64-bit
Ubuntu 14.04 LTS (trusty)		
Ubuntu 16.04 LTS (xenial)		

Note: packages for other distributions can be made available upon request. For more information, contact [services@unimrcp.org](mailto:services@unimrcp.org).

## 1.3 Authentication

UniMRCP binary packages are available to authenticated users only. In order to register a free account with UniMRCP, please visit the following page.

 <https://www.unimrcp.org/profile-registration>

Note: a new account needs to be verified and activated prior further proceeding.

## 2 Installing Deb Packages Using Apt-Get

Using the APT package handling utility (`apt-get`) is recommended for installation of UniMRCP binary packages.

### 2.1 Repository Configuration

The content of a typical configuration file of the APT repository, to be placed in `/etc/apt/sources.list.d/unimrcp.list`, is provided below.

```
deb [arch=amd64] https://username:password@unimrcp.org/repo/apt/ distr main
```

The *username* and *password* fields included in the HTTPS URI must be replaced with the corresponding account credentials.

The *distr* field must be replaced with the corresponding distribution code name such as *trusty*, *xenial*, etc.

### 2.2 GnuPG Key

For verification of binary packages, UniMRCP provides a public GnuPG key, which can be retrieved and installed as follows.

```
wget -O - https://unimrcp.org/keys/unimrcp-gpg-key.public | sudo apt-key add -
```

### 2.3 Repository Update

In order to check for updates and apply the changes in the APT configuration, use the following command.

```
sudo apt-get update
```

### 2.4 Yandex SS Plugin Installation

In order to install the Yandex SS plugin, including all the dependencies, use the following command.

```
sudo apt-get install unimrcp-yandex-ss
```

As a result, *apt-get* will check and prompt to download all the required packages by installing them in the directory `/opt/unimrcp`.

In order to install the additional data files for the sample client application *umc*, the following command can be used.

```
sudo apt-get install umc-addons
```

Note: this package is optional and provides additional data which can be used for validation of basic setup.

# 3 Installing Deb Packages Manually

UniMRCP deb packages can be installed manually using the *dpkg* utility. Note, however, that the system administrator should take care of package dependencies and install all the packages in appropriate order.

The deb packages have the following naming convention:

```
$packagename_${universion}-${distr}_${arch}.deb
```

where

- *packagename* is the name of a package
- *universion* is the UniMRCP version
- *distr* is the distribution code name (trusty, xenial, ...)
- *arch* is the architecture (amd64, i386, all, ...)

## 3.1 Package List

The following is a list of UniMRCP deb packages required for the installation of the YandexSS plugin.

Package Name	Description
<b>unimrcp-yandex-ss</b>	Yandex SS plugin to the server.
<b>unilibevent</b>	UniMRCP edition of the libevent library.
<b>umc-addons</b>	Sample en-US data files used with umc. [Optional]
<b>unilicnodegen</b>	Node information retrieval tool, required for license deployment.
<b>unimrcp-server</b>	Shared library and application of the server.
<b>unimrcp-client</b>	Shared libraries and sample applications of the client. [Optional]
<b>unimrcp-demo-plugins</b>	Set of demo plugins to the server. [Optional]
<b>unimrcp-common</b>	Data common for the client and the server.
<b>uniapr</b>	UniMRCP edition of the Apache Portable Runtime (APR) library.

<b>uniapr-util</b>	UniMRCP edition of the Apache Portable Runtime Utility (APR-Util) library.
<b>unisofia-sip</b>	UniMRCP edition of the Sofia SIP library.

## 3.2 Package Installation Order

Packages for APR, APR-Util and Sofia-SIP libraries must be installed first.

```
sudo dpkg --install uniapr_${aprversion}-${distr}_${arch}.deb
sudo dpkg --install uniapr-util_${apuverson}-${distr}_${arch}.deb
sudo dpkg --install unisofia-sip_${sofiaversion}-${distr}_${arch}.deb
```

Then, a package containing common data for the client and the server, and a package for the server should follow.

```
sudo dpkg --install unimrcp-common_${universion}-${distr}_${arch}.deb
sudo dpkg --install unimrcp-server_${universion}-${distr}_${arch}.deb
```

Next, a package containing the utility tool *unilicnodegen*, required for license deployment.

```
sudo dpkg --install unilicnodegen_${stoolversion}-${distr}_${arch}.deb
```

Next, a package containing the libevent library.

```
sudo dpkg --install unilibevent_${libeventversion}-${distr}_${arch}.deb
```

Finally, a package containing the Yandex SS plugin should follow.

```
sudo dpkg --install unimrcp-yandex-ss_${universion}-${distr}_all.deb
```

# 4 Obtaining License

The Yandex SS plugin to the UniMRCP server is a commercial product, which requires a license file to be installed.

## 4.1 License Type

The following license types are available:

- Trial
- Production
- Test and Development

## 4.2 Node Information

The license files are bound to a node the product is installed on. In order to obtain a license, the corresponding node information needs to be retrieved and submitted for generation of a license file.

Use the installed tool *unilicnodegen* to retrieve the node information.

```
sudo /opt/unimrcp/bin/unilicnodegen
```

As a result, a text file *uninode.info* will be saved in the current directory. Submit the file *uninode.info* for license generation to [services@unimrcp.org](mailto:services@unimrcp.org) by mentioning the product name in the subject.

## 4.3 License Installation

The license file needs to be placed into the directory */opt/unimrcp/data*.

```
sudo cp umsyandexss_*.lic /opt/unimrcp/data
```



# 5 Obtaining Service Credentials

In order to utilize the Yandex SpeechKit API, corresponding service credentials need to be retrieved from the Yandex Cloud portal and further installed to the UniMRCP server.

## 5.1 Service Subscription

Subscribe to the Yandex Text to Speech API.

```
https://cloud.yandex.com/docs/speechkit/concepts/auth
```

Obtain your OAuth token.

1. Log in to Yandex using your Yandex Passport account.
2. Get an OAuth token from Yandex OAuth. To do this, follow the link, click **Allow** and copy the issued OAuth token.

## 5.2 Installation of Credentials

Create a text file *yandex.subscription.key* in the directory */opt/unimrcp/data*.

```
sudo nano /opt/unimrcp/data/yandex.subscription.key
```

Store your OAuth token in the text file.

```
*****
```

The provided OAuth token is used to obtain and periodically revalidate an IAM token.

# 6 Configuring Server and Plugin

## 6.1 Plugin Factory Configuration

In order to load the Yandex SS plugin into the UniMRCP server, open the file *unimrcpserver.xml*, located in the directory */opt/unimrcp/conf*, and add the following entry under the XML element `<plugin-factory>`. Disable other synthesizer plugins, if available. The remaining demo plugins might also be disabled, if not installed.

```
<!-- Factory of plugins (MRCP engines) -->
<plugin-factory>
  <engine id="Demo-Synth-1" name="demosynth" enable="false"/>
  <engine id="Demo-Recog-1" name="demorecog" enable="true"/>
  <engine id="Demo-Verifier-1" name="demoverifier" enable="true"/>
  <engine id="Recorder-1" name="mrcpreorder" enable="true"/>
  <engine id="Yandex-SS-1" name="umsyandexss" enable="true"/>
</plugin-factory>
```

## 6.2 Logger Configuration

In order to enable log output from the plugin and set filtering rules, open the configuration file *logger.xml*, located in the directory */opt/unimrcp/conf*, and add the following entry under the element `<sources>`.

```
<source name=" YANDEXSS-PLUGIN" priority="INFO" masking="NONE"/>
```

## 6.3 Yandex SS Plugin Configuration

The configuration file of the plugin is located in */opt/unimrcp/conf/umsyandexss.xml*. Default settings should be sufficient for the general use.

Refer to the *Usage Guide* for more information.

# 7 Validating Setup

Validate your setup by using the sample UniMRCP client and server applications on the same host. The default configuration and data files should be sufficient for a basic test.

## 7.1 Setting up Folder ID

The Yandex SpeechKit folder identifier must be specified in the configuration file of the plugin, located in `/opt/unimrcp/conf/umsyandexss.xml`.

```
<synth-settings
  folder-id="*****"
  language="en-US"
  voice-name=""
  emotion=""
  auth-validation-period="3600"
/>
```

## 7.2 Launching Server

Start the UniMRCP server as a service.

```
systemctl start unimrcp
```

Check whether the plugin is normally loaded in the server logs, located in the directory `/opt/unimrcp/log`.

```
[INFO] Load Plugin [Yandex-SS-1] [/opt/unimrcp/plugin/umsyandexss.so]
```

Next, check for the license information.

```
[NOTICE] UniMRCP YandexSS License
```

```
-product name:  umsyandexss
-product version: 1.0.0
-license owner:  -
-license type:   trial
-issue date:    2018-11-17
-exp date:     2018-12-17
-channel count: 2
-feature set:   0
```

## 7.3 Launching Client

Note: the optional package *umc-addons* must be installed for this test to work.

Launch the sample UniMRCP client application *umc*.

```
cd /opt/unimrcp/bin  
./umc
```

Run a typical speech synthesis scenario by issuing the command *run bss2* from the console of the *umc* client application.

```
run bss2
```

This command sends a SPEAK request to the server and then records synthesized stream into a PCM file stored in the directory */opt/unimrcp/var*.

Visually inspect the log output for any possible warnings or errors.